

TD-4265

BLOOD GLUCOSE MONITORING SYSTEM

Strip-Ejection



FEATURES

- Strip eject function
- Before / After meal (AC/PC) presetable
- Display calendar and clock when meter standby



SPECIFICATIONS

Enzyme Type	GOD
Sample Size	0.5 μ L
Reaction Time	5 seconds
Measurement Range	20 ~ 600 mg/dL (1.1 ~ 33.3 mmol/L)
Hematocrit Range	30% - 55%
Precision	SD < 5 mg/dL (0.278 mmol/L) at < 100 mg/dL (5.55 mmol/L); CV < 5% at 100 mg/dL (5.55 mmol/L)
Accuracy	\pm 15 mg/dL if \leq 100 mg/dL; \pm 15% if >100 mg/dL
Communication	Mini-USB
Power Source	CR2032 x 1
Memory Capacity	150 sets
Dimension	125 (L) x 33 (W) x 14 (H) mm
Weight	39.8 g (without battery)
Operating Condition	10°C (50°F) ~ 40°C (104°F)
Storage Condition	-20°C (-4°F) ~ +60°C (140°F) (Meter); 4°C (39.2°F) ~ 40°C (104°F) (Strip)
Units per Carton	40
Carton Size	430 (L) x 360 (W) x 230 (H) mm
Gross Weight per Carton	10.4 kg



www.taidoc.com

TaiDoc Technology Corp.

B1-7F., No.127, Wugong 2nd Rd., Wugu Dist.,
New Taipei City 24888, Taiwan
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288