

TD-4268

BLOOD GLUCOSE MONITORING SYSTEM



±15mg/dL & ±15%

5 Sec, 1.0μL

Display Screen



Strip-Ejection

FEATURES

- Strip eject function
- Large LCD with back light
- Display both glucose level and HCT level
- Acoustic mode



SPECIFICATIONS

Enzyme Type	GDH
Sample Size	1.0 μL
Reaction Time	5 seconds
Measurement Range	10 ~ 600 mg/dL (0.55 ~ 33.3 mmol/L)
Hematocrit Range	0% - 70%
Precision	SD < 5 mg/dL (0.278 mmol/L) at < 100 mg/dL (5.55 mmol/L); CV < 5% at 100 mg/dL (5.55 mmol/L)
Accuracy	±15 mg/dL if < 100 mg/dL; ±15% if ≥ 100 mg/dL
Ketone Warning	Yes
Communication	RS232
Power Source	AAA x 2
Memory Capacity	1000 sets
Day Average	7, 14, 21, 28, 60, 90 days
Daily Alarm	4 daily alarms
Dimension	95 (L) x 55 (W) x 20 (H) mm
Weight	76.2 g (without battery)
Operating Condition	+10°C (50°F) ~ +40°C (104°F), below 85% R.H.
Storage Condition	-20°C (-4°F) ~ +60°C (140°F) (Meter); 2°C (35.6°F) ~ 30°C (86.0°F) (Strip)
Units per Carton	30
Carton Size	405 (L) x 390 (W) x 365 (H) mm
Gross Weight per Carton	6.8 kg



www.taidoc.com

TaiDoc Technology Corp.

B1-7F., No.127, Wugong 2nd Rd., Wugu Dist.,
New Taipei City 24888, Taiwan
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288