

# URiGHT

## EZTemp Infrared Thermometer



Infrared Technology




Magnetic Probe Cap  
Ear/Forehead Switchable



Fever Warning



1 sec Scan



Multi Measurement  
Modes



### SPECIFICATIONS

|                        |                                                                                                                             |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Accuracy               | ±0.2°C (±0.4°F) for the range of 35 - 42 (95°F - 107.6°F)<br>±0.3°C (±0.5°F) for the range of < 35 (95°F) or > 42 (107.6°F) |
| Measurement range      | 32.0°C - 42.9°C (89.6°F - 109.2°F)                                                                                          |
| Operation conditions   | 10°C - 40°C (50°F - 104°F) 15 - 95% non-condensing                                                                          |
| Resolution             | 0.1°C/0.1°F                                                                                                                 |
| Display                | LCD with 4-color backlit, White/Green/Orange/Red                                                                            |
| Backlit interpretation | Power on: White<br><div>32°C ≤ T ≤ 37.5°C</div> <div>37.6°C ≤ T ≤ 38°C</div> <div>38.1°C ≤ T ≤ 42.9°C</div>                 |
| Communication          | Bluetooth 4.0                                                                                                               |
| Measurement mode       | Forehead, Ear and Object                                                                                                    |
| Measurement unit       | °C or °F switchable                                                                                                         |
| Magnetic Probe Cap     | Yes                                                                                                                         |
| Power Source           | AAA x 2                                                                                                                     |
| Battery life           | At least 3,000 measurements                                                                                                 |
| Dimension              | 140mm x 35mm x 40mm                                                                                                         |
| Weight                 | 60g (w/o batteries)                                                                                                         |
| Packing                | 100 PCS/CTN/11KGs, 50x32x27cm                                                                                               |